

FTX100-L



Track Carriers
Big Power, Compact Size



Technical Specifications

GENERAL	FTX100-L
Weight with BH62	13,700 lbs.
Weight with BH74	13,975 lbs.
Weight with BH85	14,250 lbs.
Length of Tractor Only	129.5"
Width of Tractor Only	71"
Width with BH62	71"
Width with BH74	74"
Width with BH85	85"
Travel Speed (low / hi)	3.3 / 5.8 mph
ENGINE	
Model	Kubota V3800DI-T 97HP
Number of Cylinders	4
Torque	240 lbs-ft @ 1500 rpm
Cooling	Liquid Cooled
Fuel Tank Capacity	46 Gallons
Oil Filter	Spin-On Type
Air Cleaner	Dry Type Dual Element with Pre-Cleaner
HYDRAULIC SYSTEM	
Hi-Flow Pressure	5800 psi
High Flow	39 gpm
Auxiliary Pressure	3400 psi
Auxiliary Flow	19 gpm
Hydraulic Reservoir	23 gallons
UNDERCARRIAGE	
Ground Clearance	14"
Track Base	71"
Track Pad Width	16"
Ground Pressure (w/o attachment)	5.3 psi
Rock Guards	2 Piece Full Length
Rollers	1 Top \ 6 Bottom

This small but powerful carrier is able to run many skidsteer attachments: Bull Hog® Mulchers, Stump Hog, Dozer Blade, Grapple, Tree Shears, Rotary Mowers and more.

FEATURES

- Protective Cab Mower Door
- Front and Rear Lighting
- Easy Swing Out Brush Door
- Pressurized cab
- Steel tracks for Strength and Durability
- Easy access to the engine compartment

APPLICATIONS

- Land Clearing
- Forestry Applications
- Orchard Clean-up and Removal
- Prairie and Wetland Restoration
- Agricultural Preparation and Land Development
- Wild Fire Urban Interface Mechanical Fuel Treatments
- Mulch Brush, Branches, Slash, Standing and Fallen Trees, Root Balls, and Stumps

ACCESSORIES

- **Standard Winch** - Excellent for pulling machines out of difficult situations, or skidding logs.
- **Skidder Winch** lifts logs higher in the air for easier skidding.
- **Ripper** - Designed to pre-rip tough soil or frozen ground.
- **Rear Grapple** - Moving debris, rock and brush piles. Log loading and unloading, skidding logs.
- **Bucket** - Scooping and carrying small material on hard surfaces, clearing debris, rocks and trees.
- **Front Grapple** - Transport/ placing landscape materials, tree removal and moving debris, rocks and brush piles.



- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Safety Is The Responsibility Of The Operator.
- Always insure that your carrier manufacturers safety features, including Falling Object Protection, and Roll-Over Protection meet your job safety requirements.
- Specifications subject to change without notice.
- LEXAN® is a registered trademark of General Electric Company.

3/08



3460 Grant Drive
Lebanon, OH 45036
www.fecon.com
E-Mail: sales@fecon.com



Phone: 513.696.4430
Fax: 513.696.4431
Toll Free: 800.528.3113