

# FTX440



**Crawler Mulcher**  
**Maximizing Productivity  
and Uptime In The Woods**



# Technical Specifications

GENERAL		
Track Pads	24" / 600 mm	36" / 900 mm
Weight Tractor Only	44,100 lbs.	47,500 lbs.
Weight with BH350	54,100 lbs.	57,500 lbs.
Length Tractor Only	17' 1"	17' 1"
Length with BH350	23' 2"	23' 2"
Height	10' 9"	10' 9"
Width Tractor	8' 6"	10' 5"
Width with BH350	9'	9'
Ground Clearance	21"	21"
Ground Pressure	7.7 psi	5.5 psi
Travel Speed (Lo/Hi)	2.6 / 3.8 mph., Infinitely Variable	
Track Gauge	78"	90"
ENGINE		
Model	Caterpillar® C-13 Tier III	
Power	440 hp @ 2100 rpm	
Cylinders	Inline 6	
Fuel Tank	175 gal	
Fuel Consumption	14 - 22 gph	
Cooling	Auto-reversing fan	
PTO	2350 ft-lbs, 1320 rpm max	

## FEATURES

- Robust undercarriage utilizing Caterpillar® D6H and 325 components with Bonfiglioli® 713 final drives
- High visibility cab w/ 1/2" Lexan Marguard windows.
- Air suspended heated seat, climate control, AM/FM/CD radio.
- Custom, interactive Parker IQAN® control system for optimal machine performance, quick operator feedback, and ease of troubleshooting.
- Rear camera w/ color monitor.
- Safety Certifications: ROPS - ISO 8082 2003, FOPS - ISO 8083 1989, OPS - ISO 8084 2003-05-01.
- BH350 Mulcher w/ hydraulic push bar and trap door; adjustable skid shoes.

## OPTIONS

- Available track pads: 24" double, 28" double, 32" triple, 36" triple.
- GPS
- Engine positive air shutoff
- Hydraulic winch 30,000 lb. capacity
- Arctic Cold Weather Package including engine coolant heater, Hydraulic tank heater, and snow canopy.

## ADVANTAGES

- Delivers maximum power to the mulcher through a PTO driveline protected with a fluid coupler.
- Engine rpm is reduced through an industrial gear box to achieve optimal rotor torque at the mulcher under maximum loads.
- Patented synchronized interface between the mulcher and crawler allows full range of motion through lift and tilt functions.
- Fast and direct access to maintenance and service points by large doors, a sliding cab and a swing-out hydraulic cooler.
- Comfortable cab, user-friendly controls & exterior cab lighting.

## APPLICATIONS

- Land Clearing
- Forestry Applications
- Orchard Clean-up and Removal
- Prairie and Wetland Restoration
- Agricultural Preparation and Land Development
- Wild Fire Urban Interface Mechanical Fuel Treatments
- Mulch Brush, Branches, Slash, Standing and Fallen Trees, Root Balls, and Stumps



- Operators cab must be protected with both properly maintained LEXAN® Glass (or equal) and Falling Object Protection.
  - Safety Is The Responsibility Of The Operator.
  - Specifications subject to change without notice.
- LEXAN® is a registered trademark of General Electric Company.

