



STCH - STCH/SD

Stone crushers for tractors between 180 and 300 HP with a max working depth of 16 inches.

Standard equipment: double side transmission, PTO drive shaft with cam clutch, gearbox with freewheel, adjustable skirts, hydraulic rear hood, adjustable counter knives. In addition, for the **STCH/R/SD** model: inner plates in Hardox steel, skirts with replaceable Hardox sole, ploughshares made of special steel, adjustable three point linkage.

Options: hydraulic top link.

Notes: For their correct usage, a creeper gear transmission is recommended.




STCH

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Working depth inches (max)	Teeth q.ty/type STC+STC/SD
	Min	Max							
STCH 200	180	280	1000	79	101	9480	20	16	46STC+4STC/SD
STCH 225	200	280	1000	89	110	10009	20	16	52STC+4STC/SD
STCH 250	220	280	1000	98	120	10539	20	16	58STC+4STC/SD

STCH/SD

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Working depth inches (max)	Teeth q.ty/type STC+STC/SD
	Min	Max							
STCH-SD 200	180	300	1000	79	101	9789	20	16	46STC+4STC/SD
STCH-SD 225	200	300	1000	89	110	10517	20	16	52STC+4STC/SD
STCH-SD 250	220	300	1000	98	120	11465	20	16	58STC+4STC/SD

The data refers to the machine without options.



Rotor type STCH



Tooth type STCH



Tooth type STCH/SD